



|   |  |
|---|--|
| <b>Product Code</b>   | CTL-GLD-8083   |
| <b>Description</b>  | In-wall Stop Valve with Adjustable Wall Flange, Size 15 mm   |
| <b>Flow Rate</b>  | 68.39 LPM @ 3 bar  |
| <b>Recommended Water Pressure</b>   | 0.5 Bar - 5 Bar  |
| <b>Operating Knob</b>   | Swarovski Crystal  |
| <b>Brass Specification in Percentage</b>  | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b><br/>Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)"</p> |
| <b>Cartridge Specification</b>  | <p>"Fittings : Components have WRAS Approved for food grade conformity with Brass Housing and Spindle<br/>Life Cycle EN 200: 200,000 cycles (Standard)<br/>- 5.0 LAC Cycles as per EN 200**"</p>   |
| <b>Water Tightness</b>  | 16 bar (Pass)  |
| <b>Pressure Resistance</b>  | 25 bar (Pass)  |
| <b>Finish</b>   | <p>"Plating: Nickel-10.0 micron Chromium-0.3 micron<br/>Salt Spray (500 hrs + Validated)<br/>Adhesion (Pass)"</p>  |
| <b>Available Colour Finishing</b>   | Full Gold (GLD), Chrome (CHR)  |
| * As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy  |  |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |  |