



Product Code	OHS-CHR-1743
Description	LED Single Function 250X250mm Square Shape Overhead Shower
Flow Rate	15.51 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Wall Mounting
Spray Modes	Single Function
Material Composition Specification in Percentage	<p>“Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>ABS Specification Specific Gravity g/cm² (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)”</p>
Technology	<p>“A light emitting shower which transforms the stream of water into beautiful waterfall of light.</p> <ul style="list-style-type: none"> • Hydro Power: Powerful electric energy for LED, which is generated by water power. Does not require any battery or electrical power supply. • LED: The sensitive shower light changes its colour with change in temperature. <ul style="list-style-type: none"> - Water glows Red when temperature is above 42°C - Water glows Purple when temperature is between 32-42°C - Water glows Blue when temperature is less than 32°C • Rain: Immersing your body in a heavenly rain, experience nature’s downpour. Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.”
Finish	“Salt Spray (350 hrs + Validated) Adhesion (Pass)”
Available Finishing	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	