



Dreduct and	CND OLID 51440DIZ
Product code	SNR-CHR-51443PK
Description	Blush Wall Mounted Sensor faucet with Control Box & Pre-mixed Water Supply Kit (Battery Operated)
Water Supply	Hot & Cold (2 inlets)
Water Temperature	Maximum 65 °C
Inlet Water Connection	1/2"BSP / 15mm
Recommended Water Pressure	1.0 Bar - 5.0 Bar
Flow Rate	8.50 LPM @ 3 bar
Material Composition Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)  Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)  Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)  Brass Pipe as per IS:407-1996 Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)
Solenoid Valve Specification	Operating pressure 1.0 - 5.0 bar  Nominal Voltage : 6 Volt DC  Low power consumption : Bi-stable pulse controlled
IP rating	Protection against intrusion (control box) IP 65 Protection against intrusion (sensor eye) IP 67
Electronic Parameter Setting Procedure	Red button on Control Box
Adjustable Parameters	Only Detection Range: 100 - 300MM, default: 150-180MM,
Power Source	6 Volt Battery - (4 *1.5V AA cell)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Aerator Size	WRAS, ACS Approved (M16.5X1)
	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM),
Available Color Finishing	Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.